

# **SpeedWash™**



## **Power Washers**



**2900 psi** - Model G007899 (50-State & Canada)

UPC: 696471077315

**3200 psi** - Model G007900 (50-State & Canada)

UPC: 696471003413



## **Included Attachments:**





## **FEATURES**

#### **ERGONOMIC SPRAY GUN WITH PowerDial™**

- Four application settings for optimal cleaning performance
  —car, wood deck, concrete, soap
- Inverted trigger with cushion grip for extended use

#### **POWERFUL GENERAC OHV ENGINE**

Delivers maximum cleaning performance and reliability

#### **HIGH PERFORMANCE BRASS HEAD AXIAL CAM PUMP\***

- Lasts up to 2x longer than aluminum head pumps
- Convenient, easy-to-reach pump connections

#### **TIME SAVING ATTACHMENTS**

- Power Broom\*
- Turbo Nozzle
- Soap Blaster

#### 25' ULTRA FLEX HOSE

- Non-kinking
- Non-marring
- Abrasion Resistant

<sup>\*</sup> Only included on the 3200 psi-Model G007900

2 of 2

# **GENERAC®**

## 2900 psi • 3200 psi

# **specifications**

#### PRESSURE AND FLOW

Outlet Pressure (psi/bar)	2900/200 3200/221
Flow Rate (gpm)/(L/min)	2.4/9.0 2.7/10.2

#### **ENGINE**

Manufacturer	Generac
Displacement (cc)	196
Туре	4 cycle/OHV
Orientation	Horizontal
Lubrication Method	Splash
Low Oil Shutdown System	No
Fuel Capacity (gal/L)	0.8/3
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	20/0.6
Recommended Engine Oil	10W-30/SAE 30
Throttle Control	Fixed Speed
Choke	Manual
Starting Method	Recoil Pull Start

#### **PUMP**

Туре	Axial Cam
Material	2900 - Aluminum 3200 - Aluminum with Brass Head
Maximum Water Supply Temperature (°F/°C)	100/38

#### HOSE

Туре	Polyurethane
Length (ft/m)	25/7.6
Diameter (in/mm)	0.25/6.4
Rating (psi/bar)	3400/234
Connectors	M22

#### **DETERGENT SYSTEM**

Chemical Tank	Yes
Chemical Tank Size (gal/L)	0.5/1.9

#### **NOZZLES**

Nozzla Deceriptions	0°, 25°, 40°, Soap, Soap Blaster,
Nozzle Descriptions	Turbo, and Power Broom*

#### **GUN & LANCE**

Gun Type	PowerDial™
Gun to Lance Connection	M22
Gun to Hose Connection	M22
Lance connection to Hose	Quick Change
Lance Length (in/cm)	20/51
Lance to Nozzle Connection	Quick Change

#### FRAME & MISC.

Handle	Fixed - Click In
Frame Construction	Steel
Wheels - Never Flat (in/cm)	1.75 x 10/4.4 x 25.4

#### **DIMENSIONS & WEIGHTS**

Length (in/cm)	24.2/620
Width (wheel to wheel, in/cm)	18.9/479
Height (in/cm)	35.5/902
Unit Weight (lbs/kg)	2900 - 57/25.9 3200 - 62/28.3
Boxed Length (in/cm)	24/610
Boxed Width (in/cm)	20/508
Boxed Height (in/cm)	22/559
Boxed Weight (lb/kg)	73/33 77/35

#### WARRANTY

Warranty	3 year limited
----------	----------------



<sup>\*</sup> Only included on the 3200 psi-Model G007900