

# 3.0 kWh DCB Battery Module

MODEL NUMBER: G0080040

Build a modular backup system using the Generac DCB Battery Module for PWRcell 2 with as few as three and as many as six modules in a single battery cabinet.



## Features & Benefits

- **Environment:** Suitable for indoor and outdoor cabinets
- **Scalable:** Add more modules, over time, as customer needs evolve
- **Easy to Install:** At just 55 lbs, installers won't need special equipment to move and install these batteries



## Specifications

ELECTRICAL	
Nominal Voltage	46.8 VDC
Useable Capacity at Typical Voltage	3 kWh
Minimum Allowed Modules per Cabinet	3
Maximum Allowed Modules per Cabinet	6
ENVIRONMENTAL	
Full Performance Temperature Range (Charging)	59 to 104 °F (15 to 40 °C)
Full Performance Temperature Range (Discharging)	41 to 122 °F (5 to 50 °C)
Operating Temperature Range (Charging)	41 to 122 °F (5 to 50 °C)
Operating Temperature Range (Discharging)	14 to 122 °F (-10 to 50 °C)
Maximum Storage Temperature (< 1 mo)	122 °F (50 °C)
MECHANICAL	
Dimensions (LxWxH) - in (mm)	17.3 x 17.7 x 3.3 (440 x 450 x 84)
Weight - lb (kg)	55 (25)
Battery Chemistry	Lithium Nickel Manganese Cobalt (NMC)
COMPLIANCE	
Safety	UL 1973
WARRANTY	
Evaluated Functions/Protection	10 years or 7.56 MWh throughput (per module)

Generac Power Systems, Inc.,  
S45 W29290 Hwy. 59, Waukesha, WI 53189  
[www.Generac.com](http://www.Generac.com) | 888-GENERAC (436-3722)

REV A 01/2025

©2025 Generac Power Systems.  
All rights reserved. Specifications are subject to  
change without notice.